

Pink Batts®

Thermal insulation for ceiling and walls

Product description and typical applications

Pink Batts®, Australia's favourite insulation, are made from lightweight, flexible and resilient glasswool (sometimes referred to as mineral wool), specially designed for the thermal insulation of ceilings and walls in domestic and commercial buildings. They have the added benefit of being an effective sound absorber and so contribute to both the thermal and acoustic comfort of building occupants. The comprehensive range of sizes and R-values available ensures there is an efficient and effective Fletcher Insulation™ Pink Batt available for any application. Pink Wall Batts are stiffened to fit snugly between standard spacing wall studs – both timber and steel – without sagging and should be installed at the time of construction before fixing internal lining.

AS/NZS 4859.1:
2002 - Including
Amendment 1
Materials for the
Thermal Insulation of
Buildings

Pink Batts comply with the Energy Efficiency provisions of the BCA for all types of thermal insulation to be certified by a NATA accredited organisation.



CODEMARK™
GM-08-CM30008

Australian Building Codes Board
Certificate of Conformity



Global-Mark.com.au®
ID Number: 100577



Global-Mark.com.au®



FLI - 2007
GECA 33-2007 - Building Insulation
www.geca.org.au
Environmental Choice Australia
Certified Product

PINK BATTS
Comfort for Keeps™

Physical characteristics

Material R-value (m ² k/w)	Batt Size (mm)	Thickness (mm)	Batts Per Pack	Area Per Pack (m ²)	Coverage Per Pack (m ²)
Wall Batts					
R1.5	1160 x 430	65	16	8.0	9.0
	1160 x 580	65	16	10.8	12.2
R2.0	1160 x 430	90	16	8.0	9.0
	1160 x 580	90	16	10.8	12.2
R2.0HD*	1160 x 430	70	8	4.0	4.5
	1160 x 580	70	8	5.6	6.3
R2.5HD*	1160 x 430	90	12	6.0	6.8
	1160 x 580	90	12	8.1	9.1

Pink Batts are also available in 1160x480mm & 1200x600mm to suit various stud spacing.
*Minimum order quantity may apply.

Ceiling Batts					
R2.5	1160 x 430	115	16	8.0	9.0
	1160 x 580	115	16	10.8	12.2
R3.0	1160 x 430	140	16	8.0	9.0
	1160 x 580	140	16	10.8	12.2
R3.5	1160 x 430	160	16	8.0	9.0
	1160 x 580	160	10	6.7	7.6
R4.0	1160 x 430	175	10	5.0	5.6
	1160 x 580	175	10	6.7	7.6
R5.0	1160 x 430	215	8	4.0	4.5
	1160 x 580	215	8	5.4	6.1
R6.0	1160 x 430	250	6	3.0	3.4
	1160 x 580	250	6	4.0	4.5

Product must be installed in accordance to manufacturer instructions - refer to back of pack or www.insulation.com.au for details.

Green Star compliant

The Green Building Council of Australia (GBCA) strongly recommends third party validation of insulation products environmental merit by GECA - Good Environmental Choice Australia (www.gbca.org.au). All GECA certified products automatically achieve 100% product score in the Green Star calculators. GECA scientific research is based on function and overall environmental and human health in conformance to ISO14024. GECA certification provides a clear, credible guide to products that are sustainable and improve the quality of the environment.

Fletcher Insulation is committed to providing environmentally sustainable products. Fletcher Insulation products have Zero Ozone Depleting Potential in both manufacture and composition, complying with the GreenStar Insulant ODP Emissions credit requirement. Air quality is maintained with total Volatile Organic Compound (VOC) emissions below quantifiable levels.

AS1530.1 Test for combustibility of materials

Testing conducted by CSIRO in accordance with AS1530 Part 1 concluded that Pink Batts are non-combustible.

The BCA deemed to satisfy provisions require walls important to the structural integrity of commercial buildings to be constructed wholly of materials that are non-combustible. Fire rated (FRL) walls between tenancies and common walls of multi-level apartment buildings also must be constructed wholly of materials that are non-combustible. The BCA states that if materials used in an assembly contain combustible components, then the assembly is combustible.

Incorporating non-combustible *Pink Batts* into wall systems allows builders to gain acoustic and thermal benefits while still complying with the BCA requirement to maintain structural integrity and for minimizing risk to occupants from smoke inhalation and fire in Class 2 to 9 buildings.

AS1530.3 Early fire hazard properties of materials

Pink Batts exhibit the following characteristics when tested in accordance with AS1530 Part 3:

Ignitability Index	0
Spread of Flame Index	0
Heat Evolved Index	0
Smoke Developed Index	0-1

Moisture resistance

In the event of *Pink Batts* becoming wet, they should be dried prior to installation to obtain maximum performance and prevent damage to other building elements. *Pink Batts* absorb less than 0.2% moisture by volume when exposed to environmental conditions of 50°C and 95% relative humidity for four days.

Alkalinity

When tested in accordance with British Standard 3958, *Fletcher Insulation* glasswool products are slightly alkaline pH9 (neutral is pH7). They will not promote or accelerate the corrosion of steel or galvanised steel studs provided they are protected from external contamination.

Maximum service temperature

Fletcher Insulation *Pink Batts* have a maximum service temperature of 340°C.

Specification notes

State the following:

- Product name - *Pink Batts*
- Material R-Value required
- Joist or stud spacing
- Area involved.

Freecall SALES **1300 65 44 44** Technical Services **1800 000 878**
Email info@insulation.com.au Web www.insulation.com.au

NOTE: Fletcher Insulation Pty. Limited. reserves the right to change product specifications without prior notification. Information in this Publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but Because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given Or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application.

Fletcher Insulation Pty. Limited. ABN 72 001 175 355. TMTrademarks of Fletcher Insulation. TMFBS-1 Bio-Soluble Glass Wool is a trademark used under license by Fletcher Insulation. © Copyright 2010.

TDS27 / FI_0022_000610_1



The production of environmentally sustainable FBS-1 Glasswool Bio-Soluble Insulation utilizes approximately 70% recycled waste glass.



Low Allergen content with the ability to moderate temperature changes.



Fletcher Insulation glasswool products are manufactured from FBS-1 Bio-Soluble Glass WoolTM. FBS-1 Bio-Soluble Glass WoolTM is not classified as hazardous according to the criteria of the Australian Safety and Compensation Council (formerly NOHSC), Approved Criteria for Classifying Hazardous Substances (NOHSC: 1008) 3rd Edition. Fletcher Insulation glasswool is classified as safe to use, refer to our MSDS.



FletcherTM
Insulation